



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

PROVISIONAL PATENT APPLICATION

For

6

Systems and Methods for Digital Entertainment

Inventors:

Kevin Dowling

George Mueller

Ihor Lys

12

Frederick Morgan

Mike Blackwell

Scott Johnston

Daniel Simkin

Ian Davis

18

Attorney Docket: CKC-030.61

SYSTEMS AND METHODS FOR DIGITAL ENTERTAINMENT

Cross Reference to Related Applications

This application incorporates by reference, the entire disclosure of the following pending United States provisional patent applications:

- U.S. Provisional Patent Application No. 60/243,250 "Illumination of Liquids," U.S.
- 6 Provisional Patent Application No. 60/199,333 "Autonomous Color Changing Accessory," U.S.
- Provisional Patent Application No. 60/211,417 "LED-Based Consumer Products," U.S.
- Provisional Patent Application No. 60/221,579 "Color Changing Device and Enclosure," U.S.
- Provisional Patent Application No. 60/262,153 "Information Systems," U.S. Patent Application No. 60/242,484 "Systems and Methods of Digital Entertainment," U.S. Patent Application No. 60/262,022 "Color Changing LCD Screens," U.S. Patent Application No. 60/235,678
- 12 "Ultraviolet Light Emitting Diode Device," U.S. Patent Application No. 60/222,847 "Ultraviolet Light Emitting Diode Device," and U.S. Provisional Patent Application No. 60/268,259 "LED-Based Lighting Systems and Methods for Vehicles."

This application also incorporates by reference the entire disclosure of the following pending United States Patent Applications:

- U.S. Patent Application No. 09/215,624 "Smart Lightbulb," U.S. Patent Application No.
- 18 09/213,537 "Power Data Protocol," U.S. Patent Application No. 09/213,607 "Sensor Feedback Illumination Methods and Systems," U.S. Patent Application No. 09/213,189 "Precision Illumination Methods and Systems," U.S. Patent Application No. 09/213,581 "Kinetic Illumination Methods and Systems," U.S. Patent Application No. 09/213,569 "Illumination Components," U.S. Patent Application No. 09/213,540 "Data Delivery Track," U.S. Patent

Application No. 09/333,739 "Diffuse Illumination Methods and Systems," U.S. Patent Application No. 09/626,905 "Illumination Components," U.S. Patent Application No. 09/742,017 "Lighting Entertainment System," and U.S. Patent Application No. 09/616,214 "Systems and Methods for Authoring Lighting Sequences."

6 Background of The Invention

Summary Of The Invention

In an embodiment there is disclosed a system for imparting information using a lighting system comprising a computing device including a video display; a lighting system in communication with the computing device for producing illumination; and a software application for dynamically controlling the illumination in response to information presented on the video display so as to impart information to a user. The software application can include a game and/or objects and may allow for attachment of a portion of the lighting system to an object. The information provided by the illumination system can relate to an attribute of an object. The software application can be controlled by a second software application which can also include a game.

In an embodiment, the lighting system can include an LED and/or can include a screen upon which the illumination is projected. This screen can be a cabana. The computing system may also include a video game console.

In an embodiment, the information provided by the lighting system can be different from the information provided on the video display, either by being additive to the information provided on the video display, or duplicative of the information provided on the video display but in a different form. In an embodiment, the video display could provide no information.

In an embodiment there is disclosed a system for controlling a lighting system comprising: lighting system including a lighting fixture, the lighting system in communication with a computing device; and a software application including a software object operating in conjunction with the computing device; wherein, the software application attaches the control of the lighting fixture to the software object. The software application may include a game and the software object may comprise an object in the game. The system could also include a library of effects for use with the lighting system.

In an embodiment there is disclosed a screen for use with a lighting system comprising; a frame designed to be placed in proximity to the user of a computing system and; a material mounted on the frame; wherein the material is arranged in a manner so as to be able to reflect illumination produced by a lighting system to the user of the computing system. This screen may be shaped to form a cabana and/or a portion of a sphere and/or may be formed so as to be repeatedly assembled and disassembled. Further, the computing system may include a video display and the frame may be designed to be placed to at least partially enclose the video display, be placed behind the video display relative to the user, and/or at least partially encloses the computing system and the user.

In an embodiment the screen could further include a mounting bar for the attachment of lighting fixtures to the screen. The mounting bar may be arranged so that the lighting fixtures have a fixed point of attachment to the mounting bar. The mounting bar may alternatively or additively be arranged so that fixtures have a fixed point of projection onto the screen when attached to the mounting bar. Those lighting fixtures may comprise at least a portion of the lighting system.

In an embodiment there is disclosed a software application for use on a computing device comprising: computer code for generating a computer game on a computing device; and computer code for controlling a lighting system in communication with the computing device.

6 In another embodiment there is disclosed a method for visualizing the relative location of virtual objects within a virtual environment comprising: having a computing device; generating a virtual environment on the computing device, the virtual environment containing a plurality of virtual objects; associating with a virtual object, the illumination from a lighting fixture; and visualizing the relative location of the virtual object by the positioning of the illumination. The visualizing may include the position of the illumination corresponding to the position of the lighting fixture or the position of the illumination corresponding to the position on a surface which is illuminated by the illumination. The position on the surface may perform at least one of
12 the following: reflection of the illumination, refraction of the illumination, absorption and reemission of the illumination.

In another embodiment there is disclosed a method for enhancing the play of a computer game comprising: providing to a user a lighting system; providing to the user software for controlling the lighting system, the software being capable of interfacing with a computer game; and allowing the user to use the software to control the lighting system in a manner that enhances
18 the play of the computer game.

In another embodiment there is disclosed a lighting system for use with a software application comprising: at least one lighting fixture; and a computer application compatible with the software application, the computer application allowing for the software application to provide information to a user through illumination generated by the lighting fixture. The computer application may include computer software and/or computer hardware. The lighting

fixture may include an LED and/or may be one of a plurality of networked lighting fixtures. The lighting system may further include a mounting apparatus for holding the lighting fixture and/or a surface for the reflection of illumination.

In a still further embodiment there is disclosed a method for allowing a software developer to include control of a lighting system within a software application comprising:

- 6 providing a lighting system substantially similar to one provided to a user to a software developer; and providing an interface for allowing the lighting system to communicate with a computing device to a software developer; wherein the software developer can use the interface to include control for the lighting system within a software application. There can also be provided a library of prebuilt effects which can be used to generate a particular lighting effect on the lighting system to the software developer.

12

Brief Description Of Drawings

The foregoing and other objects and advantages of the invention will be appreciated more fully from the following further description thereof, with reference to the accompanying drawings, wherein:

FIG. 1 shows a computer user with an embodiment of a lighting system.

18

FIG. 2 shows an embodiment of a cabana for use with a lighting system.

FIG. 3 shows an embodiment of a video display with a lighting system built in for displaying illumination indirectly to a user.

FIG. 4 shows an embodiment of speakers with a lighting system built in.

FIG. 5 shows an embodiment of a lighting system which could be used herein.

FIG. 6 shows an embodiment of a video display with a lighting system built in for displaying illumination directly to a user

Detailed Description of the Preferred Embodiment(s)

To provide an overall understanding of the invention, certain illustrative embodiments will now be described, including various applications for programmable LED's and LED lighting systems. However, it will be understood by those of ordinary skill in the art that the methods and systems described herein may be suitably adapted to other environments where programmable lighting may be desired, and embodiments described herein may be suitable to non-LED based lighting. The descriptions below focus primarily on using LED lighting systems for enhancement of computer games as that term would be understood by one of skill in the art. In particular, the below embodiments focus primarily on a "first person" type of interactive game involving space battles where the software controlling the game is present on a user's computer. For example, installed on the user's hard drive or on a CD ROM or other storage media controlled by the user. One example of such a computer game is produced by Mad Dog software under the title "Star Trek: Armada." This type of computer game represents only one type of computer game which the below described systems and methods can be used in conjunction with. One of skill in the art would readily see how to apply the below described embodiments to other types of computer games. Further these games need not be present on the user's computer but could be run off of a network such as, but not limited to, the World Wide Web, the Internet, or any extranet or intranet network. In addition, one of skill in the art would understand that the embodiments described below could be used in conjunction with any type of computer software that need not be a game, but of any type of computer application. Further, the user need not be

operating a computer, but could be operating any type of computing device, capable of running a software application that is providing that user with information.

In computer games, there is typically a display screen (which could be a personal computer screen, television screen, laptop screen, handheld, gameboy screen, or other display) that represents a virtual world of some type. There is also typically a user in a real world environment that surrounds the display screen. The present invention relates to computer games and their surrounding environment.

In an embodiment of the invention described herein, the environment of a user of a computer game includes one or more light systems. As used herein "light systems" should be understood to include all light systems, including LED systems, as well as incandescent sources, including filament lamps, pyro-luminescent sources, such as flames, candle-luminescent sources, such as gas mantles and carbon arc radiation sources, as well as photo-luminescent sources, including gaseous discharges, fluorescent sources, phosphorescence sources, lasers, electro-luminescent sources, such as electro-luminescent lamps, light emitting diodes, and cathode luminescent sources using electronic satiation, as well as miscellaneous luminescent sources including galvano-luminescent sources, crystallo-luminescent sources, kine-luminescent sources, thermo-luminescent sources, triboluminescent sources, sonoluminescent sources, and radioluminescent sources. Light systems may also include luminescent polymers capable of producing primary colors.

As used herein, the term "LED" means any system that is capable of receiving an electrical signal and producing a color of light in response to the signal. Thus, the term "LED" should be understood to include light emitting diodes of all types, light emitting polymers, semiconductor dies that produce light in response to current, organic LEDs, electro-luminescent

strips, and other such systems. In an embodiment, an "LED" may refer to a single light emitting diode having multiple semiconductor dies that are individually controlled. It should also be understood that the term "LED" does not restrict the package type of the LED. The term "LED" includes packaged LEDs, non-packaged LEDs, surface mount LEDs, chip on board LEDs and LEDs of all other configurations. The term "LED" also includes LEDs packaged or associated
 6 with phosphor wherein the phosphor may convert energy from the LED to a different wavelength. An LED system is one type of illumination source.

The term "illuminate" should be understood to refer to the production of a frequency of radiation by an illumination source. The term "color" should be understood to refer to any frequency of radiation within a spectrum; that is, a "color," as used herein, should be understood to encompass a frequency or combination of frequencies not only of the visible spectrum, but
 12 also frequencies in the infrared and ultraviolet areas of the spectrum, and in other areas of the electromagnetic spectrum.

FIG 5 illustrates a block diagram of one embodiment of an illumination system 100. A processor 2 is associated with several controllers 3. The controllers 3 control the power to the LEDs 4. As used herein, the term processor may refer to any system for processing electronic signals. A processor may include a microprocessor, microcontroller, programmable digital
 18 signal processor, other programmable device, a controller, addressable controller, microprocessor, microcontroller, addressable microprocessor, computer, programmable processor, programmable controller, dedicated processor, dedicated controller, integrated circuit, control circuit or other processor. A processor may also, or instead, include an application specific integrated circuit, a programmable gate array, programmable array logic, a programmable logic device, a digital signal processor, an analog-to-digital converter, a digital-to-

analog converter, or any other device that may be configured to process electronic signals. In addition, a processor may include discrete circuitry such as passive or active analog components including resistors, capacitors, inductors, transistors, operational amplifiers, and so forth, as well as discrete digital components such as logic components, shift registers, latches, or any other separately packaged chip or other component for realizing a digital function. Any combination of the above circuits and components, whether packaged discretely, as a chip, as a chipset, or as a die, may be suitably adapted to use as a processor as described herein. It will further be appreciated that the term processor may apply to an integrated system, such as a personal computer, network server, or other system that may operate autonomously or in response to commands to process electronic signals such as those described herein. Where a processor includes a programmable device such as the microprocessor or microcontroller mentioned above, the processor may further include computer executable code that controls operation of the programmable device. In an embodiment, the processor 2 is Microchip PIC processor 12C672 and the LEDs 4 may be red, green and blue.

The controller 3 may be a pulse width modulator, pulse amplitude modulator, pulse displacement modulator, resistor ladder, current source, voltage source, voltage ladder, switch, transistor, voltage controller, or other controller. The controller controls the current, voltage or power through the LED 4. The controller also has a signal input wherein the controller is responsive to a signal received by the signal input. The signal input is associated with the processor such that the processor communicates signals to the signal input and the controller regulates the current, voltage and or power through the LED. In an embodiment, several LEDs with different spectral output may be used. Each of these colors may be driven through separate controllers. The processor and controller may be incorporated into one device. This device may

power capabilities to drive several LEDs in a string or it may only be able to support one or a few LEDs directly. The processor and controller may also be separate devices. By controlling the LEDs independently, color mixing can be achieved for the creation of lighting effects. In an embodiment, memory 6 is also be provided. The memory 6 is capable of storing algorithms, tables, or values associated with the control signals. The memory 6 may store programs for

6 controlling the LEDs 4. The memory may be memory, read-only memory, programmable memory, programmable read-only memory, electronically erasable programmable read-only memory, random access memory, dynamic random access memory, double data rate random access memory, Rambus direct random access memory, flash memory, or any other volatile or non-volatile memory for storing program instructions, program data, address information, and program output or other intermediate or final results. A program, for example, may store control

12 signals to operate several different colored LEDs 4. A user interface 1 may also be associated with the processor 2. The user interface may be used to select a program from memory, modify a program from memory, modify a program parameter from memory, select an external signal or provide other user interface solutions. Several methods of color mixing and pulse width modulation control are disclosed in U.S. Patent 6,016,038 "Multicolored LED Lighting Method and Apparatus," the entire disclosure of which is incorporated by reference herein. The

18 processor 2 can also be addressable to receive programming signals addressed to it.

There have been significant advances in the control of LEDs. U.S. Patents in the field of LED control include Ser. Nos. 6,016,038, 6,150,774, and 6,166,496. U.S. Patent Application No. 09/716,819 for "Systems and Methods for Generating and Modulating Illumination Conditions" also describes, among other things, systems and controls. The entire disclosure of all these documents is herein incorporated by reference.

In embodiments of the invention, the lighting system may be used to illuminate a real world environment. On such environment is shown in FIG. 1. In FIG. 1 a user (101) is using a computing device (103). The computing device has a video display (104). The user also has at least one lighting fixture (105) mounted nearby. Generally the lighting fixtures (105) will be mounted in a manner that the user (101) can see either the illumination projected by a lighting
6 fixture (105) directly, or indirectly, such as by bouncing the illumination off a surface (107).

The lighting fixtures in combination comprise the lighting system. The lighting system will be in communication with the computing device (103) by any manner known to one of skill in the art which can include, but is not limited to: wired connections, infrared (IR) connections, radio frequency (RF) connections, any other type of connection, or any combination of the above. In the depicted embodiment the surface (107) comprises a screen designed to reflect light.

- 12 Alternatively the screen could be, but is not limited to, a wall or other surface upon which light could be reflected. In another embodiment, the surface could be designed to absorb and retransmit light, possibly at a different frequency. For instance the surface (107) could be a screen coated with a phosphor where illumination of a particular color could be projected on the screen and the screen could convert the color of the illumination and provide a different color of illumination to the user (101). For instance the projected illumination could primarily be in the
18 blue, violet or ultraviolet range while the transmitted light is more of a white.

In an embodiment, the lighting system is placed in a real world environment (109) that includes the computing device (103) and the user (101). The real world environment (109) could be a room that includes a computer. The lighting system could be arranged, for example, to light the walls, ceiling, floor or other sections or objects in a room instead of, or in addition to lighting the surface (107). The lighting system may include several addressable lighting systems with

individual addresses. With this system, much like the surface (107), the illumination can be projected so as to be visible to the user (101) either directly or indirectly. That is a lighting fixture (105) could shine so that the light is projected to the user without reflection, or could be reflected, refracted, absorbed and reemitted, or in any other manner indirectly presented to the user (101).

6 In use, the illumination system can be used to provide information to the user (101) in response to the information being provided to the user (101) by the video display (104). One example of how this can be provided is in conjunction with the user playing a computer game on the computing device (103). The light system may be used to create one or more light effects in response to action on the video display (104). The lighting effects, or illumination effects, can produce a vast variety of effects including color-changing effects; stroboscopic effects; flashing
 12 effects; coordinated lighting effects; lighting effects coordinated with other media such as video or audio; color wash where the color changes in hue, saturation or intensity over a period of time; creating an ambient color; color fading; effects that simulate movement such as a color chasing rainbow, a flare streaking across a room, a sun rising, a plume from an explosion, other moving effects; and many other effects. The effects that can be generated are nearly limitless. Light and color continually surrounds us and the way we control and or change the illumination or color in
 18 our space can change emotions, create atmosphere, provide enhancement of a material or object, or create other pleasing and or useful effects.

It is important to note that the lighting system producing illumination in response to the information provided on the screen allows the lighting system to describe activity which is not represented on the screen in any way. The best example of this is by thing of the user (101) using the video display (104) as a viewport into a virtual environment created by the computing

device (103). In the virtual environment, something could be behind the user, however, the video display may only show a view in front of the user. The user could turn around and see the object behind them by rotating the viewport. Objects which are behind the user in this virtual environment could still be objects which a user in a real environment would be able to see because their vision is not limited by a viewport into the real environment. The view through the

6 viewport, however defines a particular positioning within the virtual world (a placement and a facing) Therefore the lighting system could show information about what is behind the user. This information is still produced in response to what is produced on the video display because the particular video display defines the user's location in the virtual world. The lighting system therefore provides information in response to the video display that is not actually pictured on the video display. In particular, it provides information that there is something not currently in

12 view of the viewport of the visual display, but present in the virtual world.

In one embodiment, the lighting system may be used to extend the area of the user's (101) vision beyond the edges of the video display. Referring to FIG. 1, the user could be playing a game where they are at the controls of a starship and there are various objects in a virtual space around them. The video display could show the view out of the supposed front of the starship showing other starships, planets, or other cosmic phenomena visible out the front of

18 the starship. In many games, however, the world is not defined solely by what is in front of the starship but the user is supposed to have a first person view into a world that surrounds them. For instance another starship could be behind the starship the user is piloting in the game. The illumination system could provide indications as to locations of other objects beyond the visual display. For example, a starship may be displayed on the video display and the starship may appear to be irradiated with a blue light. The blue light may be coming from a light source

within the game environment, possibly a nebula, that is outside the viewing parameters of the screen of the video display. The nebula may be outside the upper right hand corner of the screen for instance. The lighting system could be used to create a light source visible to the user at the appropriate location based on the apparent irradiation on the ship. In FIG. 1 This may be accomplished by having a blue light reflect off surface (107) at the point appropriate for the

6 nebula.

The illumination can be used to extend beyond the boundaries of the video display or the user's actual vision. For instance, in the game world the user's starship may be being attacked from behind. The illumination system could pass on this information to the user by flashing lights behind the user with a red color indicating to the user that they are being attacked from the rear. The user seeing the illumination as it passes over them and reflects off of the surface or

12 other objects surrounding the user. In this case there may be no indication of the rear attack on the video display and the lighting system provides the information to the user.

The example of a rear attack shows that a surface (107) may be replaced or augmented by light in the entire users environment, or by other surfaces. The entire room or environment in which the user is playing could be used to extend the effective viewing space of a computer monitor. For example, a flash of light representing an explosion could be generated behind a

18 gamer to create the feeling that the explosion actually occurred behind the gamer. This could also be coordinated with sound such that the sound and light appear to be coming from the same area of the room. Such activity can allow for a more in depth game playing environment. As discussed above the user in the game may be supposed to have a "first person" view into the game world. By surrounding the user with illumination, the user may be able to have real world space provide a simulation of that world outside the display on the video display. Further a

moving object could appear to leave the video display and continue moving. For instance, the light from an explosion could begin on the video display, and appear to race toward and even through the user.

As discussed above, the lighting system may make use of a surface or screen to provide a location of their viewing of the projected illumination. A screen may be useful because it can provide a set real world environment designed to allow easy control over the illumination outside the video display. In embodiments of this invention, there is a screen unit that is associated with the computer and that is used to reflect color output from the light system. In an embodiment, the screen unit is a cabana that is used to surround the display screen of a computer, wherein the cabana reflects back color from color lights. One embodiment of such a cabana is shown in FIG.

2. The cabana in FIG. 2 includes a frame 201 supporting fabric 203 in a rigid or semi rigid structure such as a miniature tent. The fabric could be selected to provide a high reflectivity and good visualization of light. Further, the cabana having a quarter spherical shape, or other 3 dimensional shape, can allow distance to be portrayed without use of imposed perspective. Such as design may also allow for the placement of the surface over a standard video display. The cabana in FIG. 2 also includes a mounting bar (205) upon which lighting fixtures may be mounted wither temporarily or permanently. The advantage of such a mounting bar is that the cabana could be assembled and disassembled and the lighting fixtures could be very quickly aimed to the appropriate points on the fabric (203) even if the assembler did not know the appropriate aiming of the lights. Ion one embodiment, clips or other mounting devices can be included on mounting bar (205) that only allow a particular installation of a particular fixture aimed in a particular direction. Other examples of screens and enclosures for reflecting light from the light system are set forth in appendix A. The enclosures could be anything from small,

collapsible units, to large, even building-sized, arrangements. Any enclosure designed to be associated with a display screen for a computer game and to reflect color light from a light system associated with the computer game should be understood to be encompassed by the present disclosure. In an embodiment of the invention, there may be a light screen permanently associated with a computer for reflecting light that represents an attribute of an object of a

6 program running on the computer. The screen could be a completely or partially enclose an environment, such as computer surrounded by an enclosure of white or other material. One example could be a completely enclosing arcade game setup as is known to the art. Any number of lights (lighting fixtures) may be used to light the screen. The one or more lights may include several addressable lighting systems and the projected illumination from individual lighting fixtures may be distinct, overlapped, or both on the screen. The screen itself could also contain

12 lighting fixtures not aimed at the screen for instance lighting fixtures could be placed on mounting bar (205) and aimed at the user.

There are many ways that the lighting fixtures can be arranged and lighting systems can be generated to illuminate a surface or shine directly on the user. FIG. 3 illustrates an embodiment where the lighting system (1404) is incorporated into the video display (1402). This device can be used in place of a more complicated layout of lighting units or it can be used

18 in conjunction with the other lighting units. The lighting system (1404) can be divided up into several sections to provide stereo lighting effects around the video display. For example, the lighting system (1404) can be divided into three segments, right side, left side and top. A light track could contain light control information for each of these sections such that light of any color can be emitted from any side of the video display (1402). This may be useful in extending the effects from the video display (1402) onto a wall or screen behind it. For example, if the

right side of the video display is blue the lighting on that side of the video display (1402) could also light the wall blue. Flashes of lightning that cover the entire screen could be flashed all around the video display (1402). If an automobiles headlights start on the right side of the screen and move to the left the lighting system (1404) could follow the same pattern.

FIG. 4 illustrates an embodiment where the lighting system (1504) is incorporated into the speaker (1502) of a sound system. This device can be used in place of a more complicated layout of lighting units or it can be used in conjunction with the other lighting units. The lighting unit (1504) can also be divided up into sections although the largest benefit from this device is to use it as a single lighting element to project the light in various sections of the room where the user had already placed speakers. Therefore setup of a surround sound system, as would be understood by one of skill in the art, could also allow for the setup of a surround light system at the same time. The benefits of this are apparent. The sound of an explosion traveling over the user via the speaker can be complimented by the light of the explosion traveling in the same manner.

The examples discussed above primarily relate to systems where a real world light system in the user's environment can generate light output that reflects, indicates, or is associated with objects or events in the virtual environment of a computer game. Conversely, the virtual environment can reflect events in the real world environment, such as when the lights are coupled with sensors, receivers, or other inputs for receiving data. For instance, a sensor could detect that the light from a particular fixture is being blocked indicating the user has stood up and is taking a break from the game and the fixtures should be powered down to save energy, and the user's game should be paused.

In embodiments, the light system may be associated with code for the computer game, so that the computer game code is modified or created to control the light system. Object-oriented programming techniques can be used to attach attributes to objects in the computer game, and the attributes can be used to govern behavior of the real world light system. Object oriented techniques are known in the field, and can be found in texts such as “Introduction to Object-Oriented Programming” by Timothy Budd the entire disclosure of which is herein incorporated by reference.

In an embodiment, a developer can attach the light system inputs to objects in the game. For example, the developer may have an abstraction of a light that is added to the code construction, or object, of a game object. An object may consist of various attributes, such as position, velocity, color, intensity, or other values. A developer can add light as an instance in the object in the code of a game. For example, the game object could be a ship, with attributes, such as position, size, velocity, etc. A light source can be added as an instance of the object of the game, and the light source can have attributes, such as intensity, color, and various effects. Thus, when events occur in the game that call on the object of the ship, a thread running through the program can draw code to serve as an input to the processor of the light system. The light can accurately represent geometry, placement, spatial location, represent a value of the attribute or trait or provide indication of other elements or objects.

Using such object-oriented light input to the light system from code for a computer game, various lighting effects can be associated in the real world with the virtual world objects of a computer game. For example, in a space battle game, a ship’s light source can be attached with an effect, such as sound, flashing, motion, vibration and other temporal effects. Further, the light system could include other effects devices including sound producing devices, motion producing

devices, fog machines, rain machines or other devices which could also produce indications related to that object.

In embodiments, the program code for the light has a separate thread running on the machine that as often as possible runs through the list of virtual lights and does three-dimensional math to determine which real-world lights are in proximity to reference point in the real world (e.g., the head of the user) that is projected as the reference point of the coordinate system of objects in the game. Thus, the (0,0,0) position can be the user's head in the real world and a point on the screen in the game (for instance the center of the video display and therefore the user's view into the virtual environment). The code can map the virtual environment and object in it to the real world environment, including the light system, so that events happening outside the computer screen are similar in relation to the reference point as are virtual objects to a reference point on the screen. The mapping function may be done with a function, e.g., "project-all-lights," as described in Directlight API described below and in Appendix B, that maps real world lights using a simple user interface, such as drag and drop interface. The placement of the lights may not be as important as the surface the lights are directed towards. It may be this surface that reflects the illumination or lights back to the user and as a result it may be this surface that is the most important for the mapping program. The mapping program may map these surfaces rather than the light fixture locations or it may also map both the locations of the fixtures and the light on the surface. In one embodiment screen, such as the cabana discussed above, can further simplify this mapping by providing a set and unchanging lighting system and screen that will have identical properties no matter the real world environment the system is set up in.

Each real light may have attributes that are stored in a configuration file. The configuration file may include light number, position of light, position of light output, gamma (brightness), an indicator number for one or more attributes, and various other attributes. By changing the coordinates in the configuration file, the real world lights can be mapped to the virtual world in a way that allows them to reflect what is happening in the virtual environment.

- 6 The developer can thus create time-based effects, such as an explosion. There can then be a library of effects in the code that can be attached to various game attributes. Examples include explosions, fades in and out, etc. The developer attaches the effects to virtual lights in the game. For example, when an explosion is done, the light goes off in the game, reflecting the destruction of the object that is associated with the light in the configuration file.

- 12 To simplify the configuration file, various techniques can be used. In embodiments, hemispherical cameras, sequenced in turn, can be used as baseline with scaling factors to triangulate the lights and automatically generate a configuration file without ever having to measure where the lights are. In embodiments, the configuration file can be typed in, or can be put into a graphical user interface that can be used to drag and drop light sources onto a representation of a room. A developer can create a configuration file that matches the fixtures with true placement relative to a user's coordinate in the real room. For example, once the
18 lighting elements are dragged and dropped in the environment, the program can associate the virtual lights in the program with the real lights in the environment. An example of a light authoring program to aid in the configuration of lighting is included in U.S. Patent Application No. 09/616,214 "Systems and Methods for Authoring Lighting Sequences." Color Kinetics Inc. also offers a suitable authoring and configuration program called "ColorPlay."

Further details as to the implementation of the code can be found in the Directlight API document attached hereto as Appendix B. Directlight API is a programmer's interface that allows a programmer to incorporate lighting effects into a program. Directlight API is attached in Appendix B and the disclosure incorporated by reference herein. Object oriented programming is just one example of a programming technique used to incorporate lighting effects. Lighting effects could be incorporated into any programming language or method of programming. In object oriented programming, the programmer is often simulating a 3D space in the screens. The 3D space continues throughout the room the gamer is in and beyond to virtual infinity. In this 3D space, the programmer may place an object, such as a starship, as well as a virtual light, such as a nebula, sun, star, other star ship, photon beam, weapon, explosion plume or other light generating object.

In the above examples, lights were used to indicate the position of objects which produce the expected light or have light attached to them. There are many other ways in which light can be used. The lights in the light system can be used for a variety of purposes, such as to indicate events in the game, to indicate levels or attributes of game objects, such as characters, ships, weapons, shields, health, playing pieces, environments, rooms, or other objects. For instance the lights could turn to a particular color (for instance green) representing the shield strength of a starship. As the shields were slowly knocked down by enemy fire, the lights could change color or slowly fade out indicating the shield strength is fading. The lights can be used for aesthetic purposes, such as to connote a mood for an object or an environment in the game. For instance, the lights could change color to indicate the passage of time in the game world, or could produce lighting effects to simulate environment effects. For instance the lights could have an appropriate flicker to indicate that it is raining in the game world. A wide range of effects can be

used, each associated with a particular object or event in the game. The lighting system could provide further indications such as by triggering a real world fog machine, when the virtual environment is supposed to be foggy.

In embodiments, there may be an optional override mechanism that takes over one or more lights and direct them to do something regardless of what the virtual light source is intended to do. This may be useful when the program requires all of the lights in the system change to a particular color. For example, the game may be played out in a space environment where the starship is lighted blue from a nearby nebula when suddenly the ship is attacked by another ship. The program can instantly change all of the lights in the system to flashing red to indicate a red alert. The pulsation of the lights may be coordinated with the sound of an alarm or other sensations to further immerse the user.

In embodiments, an object, such as a ship's light source, can be associated with lights outside the game or any purposeful lighting setup, such as room lights. Any real world lighting fixture could be used as part of a lighting system as discussed herein. Optionally, direct access to outside lights can override the light source in the game. For example, the video display can provide user interface information, such as red alerts, strength of a unit or other attributes of game objects through the lights. In effect the video display could be disabled and only lights could be used. Such an embodiment could enable a computer game to be created which uses the lights as the sole source of information, or alternatively, the video display device could be disabled to indicate a particular situation has occurred. Returning to the starship example. A situation could occur where the starship has been "blinded" as part of the game actions. This may result in the forward view being unavailable to the user. However, the user can still navigate the starship using the lighting system. This ability can add a depth of play that has

previously been unavailable to a computer game because the screen video display has previously been the only device which can provide visual feedback.

It is also possible to have light system lights that are not attached to objects in the game, such as to indicate another environmental condition, such as the end of the work day, sunset, sunrise, or some other indicator that is useful to a player immersed in the game. The may also
 6 provide mood or aesthetics such as projecting the presence of a person, creature object, or other thing such as by an aura or their traits of good and evil. These traits could be associated with colors and intensities. Approaching a dangerous object could also have the lights switch to a warning mode (such as flashing red) to warn the user of the danger.

In yet another embodiment, the lights could act as a detriment to game play to show various conditions. For instance, in certain computer games the user is supposed to be hampered
 12 because they have carried out a particular action in the game. For instance the sound may be cut off because the user was too close to a virtual explosion and they were “deafened” by it. Such feedback is common, often with the user’s video display acquiring random noise or color to disorient the user. One example of how lights could be used if a player was too close to an explosion, the lights could provide for blinking “spots” to distract the user and degrade their game play. Alternatively, if the game universe indicated the user was supposed to be drunk,
 18 disoriented, or otherwise distracted, the lights could flash or change color in disorienting patterns to actually distract the user from their game play.

In the embodiments above, a system is primarily discussed where the computer code is designed to interact with a three-dimensional virtual world of which the user is part. The code works well to translate from the three dimensional objects into the real three-dimensional world. To hook up the lights to a two-dimensional world, additional programming may be required and

additional conditions may need to be put into effect. In a two-dimensional world, the code is not necessarily designed to place the real world user at a reference point, so the code may need to adapt to place the real world user in the environment in the same position as the virtual “user” (called a character) in the game. Alternatively, it may be undesirable to control the lighting systems illumination to indicate what the user’s character is seeing in the virtual world. Instead,

6 the lighting system may extend the world the user sees. One example of a 2-D game is “Diablo” produced by Blizzard software. In this game the user looks down on a map which contains a representation of the character the user is controlling. As opposed to the first person view discussed above, in this game the user has a third person view looking down on the character that is supposed to be them. The screen then provides a perspective layout of a game world of which the character is a part. If the illumination system provides the view as the character would see it,

12 the user may be confused (for instance a fire could be burning at the lower right corner of the screen but be represented by a lighting fixture behind and to the left of the user, based on the facing of the character, the character could then turn in place resulting in minimal change of the information on screen, but a dramatic shift in the illumination produced by the lighting system. It may therefore be desirable to extend any perspective or view of a 2-D game in a manner so that the lighting system illuminates in a manner to conform with the view on the video display.

18 Following with the above example the lights may track to follow the fire off screen as the character moves away from the fire. This could occur by defining a “plane of the game” representing the game world as if the user was not present at all and only the character existed. Therefore as the character in the game moved up and left from the fire, the fire appears to move, via the lighting system, down and to the right.

In one embodiment of the invention, the lighting system can be replaced or augmented by lights already present in the real world environment. For instance, one can create a game that involves the use of the lights in the house. One can use the game itself as a user interface for the lights in the house. A good example might be a horror game where when the lights go out in the game environment, they also go out in the real world room. Such an environment could be

6 highly engaging to a user who is placed even more within the virtual world in which they are playing by having that world truly interact with the real world where they are.

The real lights in the house could be made game objects for the game itself, or particular light arrangements could be created for the purposes of playing particular games. Thus, a version of a game such as “pong” or other simple game can be played with an array of lights in the light system, with the lights in the array serving as “pixels” analogous to the virtual

12 environment on the screen. In such embodiments it may be unnecessary to use the screen to play the computer game. Alternatively, one player could use the screen to control the game being played, while other players are totally immersed in a gaming environment. As discussed above, a player could be playing a horror game while the players in the next room are experiencing the light sensations from his play without control over the game environment. Essentially they can experience the game play as a third party along for the ride in the game. Further the layout of

18 lights in a house could denote the parameters for a particular game. For instance, a game could be created where the user is fighting off evil monsters in their own home and the lighting in their home is acting in the same manner as the lighting in the game. Such a game environment could be created by receiving information about the location of lights in a house, and generating the game world to conform to that lighting.

It would be easily understood by one of skill in the art that this multi party experience could be extended to multi party competitive games such as those commonly played across networks. It could be the case where a user is actually trying to effect the real world environment in which another user is playing. For instance, in the game a first user could be trying to disable an opponent's ship by knocking out it's ability to perceive the world around it.

- 6 For instance it could knock out the ships forward or rear views. In the real world a second player could actually have various views knocked out (lights being disabled) as the first player accomplishes his goal. In an even more realistic example, the first user could be trying to turn the lights out on the second user. The first person may also directly affect the other persons room lights by, for example, turning the lights off or changing their color, or the first person may indirectly change the lighting conditions in the other persons room by, for example, getting close
- 12 to the other persons virtual room and tripping a sensor. The first person may also be carrying an object that generates light or reflects light. This object may trigger the lighting in the other persons room to indicate or warn the other person of the first persons presence.

- An embodiment may also be an indicator light. A problem with gaming systems and other computer systems in general is the lack of space on a video display. There is only a limited amount of dials, indicators, or other status checks that can be placed while still providing a user
- 18 with a reasonable play environment. A gaming program, for example, may generate a indicator on the video display to indicate a parameter such as the health of the ship, the fuel remaining, the strength of the shields or other parameters. This information is important to the user, however, the indicator takes up valuable video screen leaving the actual game play area a diminished space an possibly cutting off important user views. An embodiment of the invention may be an indicator light or set of lights that sits on top of the computer screen, for example.

FIG. 6 depicts a computer screen 602 which could be useful to provide such indicators. An information system 601 may be associated with the computer screen 602. The information system 601 may contain lighting elements 603. In an embodiment, the lighting elements 603 may be aligned as separate lights that can turn on and off and or change in hue, saturation or intensity. For example, the information system may have several independently controllable

6 LED systems and these systems could be controlled in such a manner as to change color to indicate information. For instance, the information could be communicated to the information system through gaming software to indicate the health of an object or person, indicate shield strength, indicate fuel level or any other information that may be useful for the user. In an embodiment, the information system may take the form of a single light source indicating one or more parameters.

12 The indicators could perform a wide variety of functions including turning on and off, changing color, changing intensity and or other functions to replace or additively improve upon the output from the indicators. For instance, a user's health in the game could be displayed by a number in the corner of the user's screen but could also be represented by a light that changes from green to red as the virtual health drops and flashes insistently when the user's virtual health is perilously low.

18 In another embodiment, a shield could start as white and fade to another color as it loses strength. You could start to see "holes" in a shield that are shown by different colors in the room in the direction where the shield is weak allowing a user to quickly realize how to turn to bring more powerful shields to face an enemy. You could also see a jump into "warp" speed where the front of the room turns bright and then the bright light flashes towards the back of the

room for example. In a racing game, speed could also be simulated as streetlights on screen race down a row of lights off to one side of the user.

In an embodiment, a lit enclosure for the device on which the game is being played changes as an indicator. Game console buttons could also blink to indicate a combination. Like a color-note organ (such as described below), this embodiment could be used in training mode to
 6 teach combinations.

Although the FIGS and description above show primarily computer games, it would be clear to one of skill in the art to carry the system into other types of computing devices and environments. A computing device can include, but is not limited to, any type of computer, a console game system (such as the Playstation series manufactured by Sony), a Personal Digital Assistant (PDA), a telephone, a WebTV or similar system, a thin client, or any other type of
 12 system on which a user is able to carry out applications where a lighting system could enhance the display provided to the user. This could even be systems where the lighting system provides the only source of visual information to the user.

For console game systems, one of skill in the art would understand that libraries customized onto the proprietary chipsets for console games that drive light system output, similar to the Directlight programmer's interface could be created without undue experimentation.
 18 Console games generally have proprietary chipsets so it may be necessary to generate custom libraries for these systems. The systems and libraries for the consoles could function in much the same way as a PC based game. The console may include a USB, serial, parallel, firewire, optical, modem or other communications port to communicate with the lighting system. The lighting information could also be sent through a controller port. A controller port may be used for a controller communication as well as lighting control information. Separate controller ports

could also be used. For example, a first controller port may be used to communicate with a controller and another controller port may be used to communicate with the lighting system.

Many games and computer systems include input devices such as a joystick, mouse, keyboards, gloves, tactile mouse, dance pads, or other input devices. These devices are generally used by a user to control aspects of a game or other parameter of a computer program. Each of
 6 these input devices could also be configured to affect the room lights. For example, a mouse could be used to control the lights in a room. As the mouse is moved the lights in the room could respond, or as the user dances on a dance pad the lights could generate a color representation of their dance. For instance, their impact force with the pad could translate to an intensity while their position translated to a color. The input device may also direct sound simultaneously or in conjunction with the light.

12 In an embodiment of the invention the lighting system could also be associated with room inputs that could be associated with the virtual environment such as a microphone, camera, heat, cooling or other room inputs.

The embodiments discussed above relate primarily to games involving real-time simulation and for such types of games there are numerous applications for lighting systems. For instance: flight games could use indicators for controls or important statistics like fuel level;
 18 racing games could have motion or indicate third party activities like the approach of police vehicles: skateboarding, snowboarding, or other performance sport simulators can have indicators of movement, indicators of third party actions, or rewards such as flashbulbs for particularly fine performances. Other types of simulators can use lighting systems including, but not limited to, roller-coaster simulations, closed booth arcade simulators, or location-based entertainment games (large games inside a booth with multiple players). Further, it would be

understood by one of skill in the art that the above are merely a limited overview of possibilities and there are many more applications that could be performed without undue experimentation.

These types of games are typically 3D rendered and have objects with attributes as well as events. Code can track events and attributes, such as explosions, bullets, health, other people, patterns of light, and/or secret passageways. The code can then map from the virtual world to
 6 the real world. In embodiments, the system can add to the virtual world with real world data, such as from sensors or input devices. Also, by using the light system as an indicator, it is possible to give information through the light system that aids the user in playing a game or otherwise interacting with a virtual environment. For example, a light could flash or change color to indicate the coming of an event that would otherwise be a surprise to a user who does not have the light system when playing the game. The indicator functions of the light system can
 12 be coupled with three dimensional sound (such as surround sound) to provide enhanced real world effects that relate to events and attributes in the virtual environment.

In other embodiments the lighting systems can be used in conjunction with puzzle games, a developer can create a room-puzzle using the light system in a room or other environment to create games with the lights. For example, the room lights can reflect the color of puzzle elements in the virtual world, creating a correspondence between the virtual and the real world
 18 puzzle elements. One can manipulate real-world elements without the display on the computer. (In embodiments, one can play a game, such as pong, with the actual lights using a joystick attached to the computer. The code for the game can provide the interactive aspects of the game, then hand control signals to the light system so that the lights act as game elements in the real world environment. For example, one can create an array of lights on the ceiling, which could send light elements across the room). The lights can act as “pixels” in an array on the ceiling,

wall or floor. In embodiments, the arrays could be established in a variety of rooms, so that light output moves from room to room in response to the user's interaction with the input device or sensor of the computer game or other virtual environment. Light strips can be used for game elements, as can other light system configurations.

A real world light system can be used to respond to input from objects in classic arcade
 6 computer games, such as Pacman, pong, asteroids, space invaders, breakout, and similar games, in each case enhancing the user experience by providing either aesthetic or indicator functions. Light systems can also be used with any other game type, such as casino simulators, video poker, sandbox games, railroad tycoon games, simulation games like Sim City, and the like.

In embodiments, light systems can be used with role-playing games, such as two-
 dimensional games like Diablo and three-dimensional games like EverQuest (a massively multi-
 12 player online game). In such games, real world lights can be mapped to attributes of humans or objects in real world. The lights can provide more interaction with other humans or non-human players. Attributes and events can be a wide variety of things, such as indicating health, casting a spell, indicating shield strength or presence, displaying a fireball, or other effects. Further in multiplayer games at a single location, the lights can be used to provide functions to the players by indicating the seat of a player you would like to meet in person for example.

18 Further, in many multi player games (such as Everquest) items and characters have become collectible. Everquest Avatars are popular where there are characters that have characteristics that are acquired over time. Some are sold for large amounts of money on the Internet. The room lights of a light system can reflect the attributes of an avatar, such as a powerful blue to represent a "good" character, or a dark red to reflect "evil." Any attribute, ranging from personality traits, to strength, speed, location, health, constitution, intelligence,

stamina, wisdom, or other attributes can be reflected for a given avatar by the room lights in the real world in correspondence to the attributes of the avatar in the virtual world. In embodiments, one can make collectible patterns or effects that associate with characters, objects or events.

Thus, a virtual world object or character could have a “signature” or “trademark” color effect that takes place each time the character appears in the virtual world or does a particular thing in

6 the virtual world. You could accrue an aura for a character over time as part of a character’s attributes. Light could be used to portray abstract character traits. In multi-player environments like arcades, people could glow according to the aura of the character they are playing. Objects could embody those traits, and you might need to have a particular object or trait to allow you to see the indicator for another object.

In adventure games, which typically involve solving a puzzle in an environment –
12 environmental lighting could be part of the puzzle. The light system could give clues required or helpful to solve the puzzle.

In sports games, a light system in the real world can serve as an event indicators (flashbulbs, cut scenes – could shift lights) or as attribute indicators (indicating health of a player, number of fouls, etc.).

In turn-based strategy games, a light system can indicate events or attributes, or provide
18 aesthetic effects. Those could include the day and night cycle, something catching fire (where you see event first in the lights, then in virtual world), a warning from behind that comes first (such as to indicate a glowing light sabre of a player behind you), or other events or attributes.

In fighting games, lights in the real world can indicate seeing someone’s shadow before they jump over you, moving lights after a “kill” or powerful blow, or indicating declining or improving health or presence of special attributes (such as shields or spells). Further, moving

shadows or illumination created by the lights could indicate the position of a tag team partner. It is important to note that the absence of light (a shadow) can also be part of the illumination and illumination as described herein. The absence of any intensity of any color is simply on possible illumination condition.

In children's games, room lights and a room sound system can reflect color and intensity
 6 attributes of elements of the games, which can include games to teach children about different colors and sounds.

As was discussed above, computer games provide merely one type of computer program in which a lighting system can provide enhancement and additional information. There are many other types of computer programs which the use of a lighting system can benefit

A similar embodiment to computer games is auction-type, real "games," such as Internet
 12 auctions, such as E-bay. Lights could be used as an indicator of an event or characteristic, such as having the highest current bid, or a winning bid. Online gambling establishments could also use the lights so as to provide a Casino like environment in the user's home.

Architectural visualization and other solid modeling environments are encompassed herein as embodiments. In these virtual environments lighting is often relevant both in a virtual environment and in a solid model real world visualization environment. Scale physical models
 18 in a room of lights can be modeled for lighting during the course of a day or year or during different seasons for example, possibly to detect previously unknown interaction with the light and various building surfaces. Another example would be to construct a replica of a city or portion of a city in a room with a lighting system such as those discussed above. The model could then be analyzed for color changes over a period of time, shadowing, or other lighting effects. In an embodiment, this technique could be used for landscape design. In an

embodiment, the lighting system is used to model the interior space of a room, building, or other piece of architecture. For example, an interior designer may want to project the colors of the room, fabric or objects in the room with colors representing various times of the day, year, or season. In an embodiment, a lighting system is used in a store near a paint section to allow for simulation of lighting conditions on paint chips for visualization of paint colors under various conditions. These type of real world modeling applications can enable detection of potential design flaws, such as reflective buildings reflecting sunlight in the eyes of drivers during certain times of the year. Further, the three-dimensional visualization may allow for more rapid recognition of the aesthetics of the design by human beings, than by more complex computer modeling.

Solid modeling programs can have virtual lights. One can light a model in the virtual environment while simultaneously lighting a real world model the same way. For example, one can model environmental conditions of the model and recreate them in the real world modeling environment outside the virtual environment. For example, one can model a house or other building and show how it would appear in any daylight environment. A hobbyist could also model lighting for a model train set (for instance based on pictures of an actual train) and translate that lighting into the illumination for the room wherein the model train exists. Therefore the model train may not only be a physical representation of an actual train, but may even appear as that train appeared at a particular time. A civil engineering project could also be assembled as a model and then a lighting system according to the principles of the invention could be used to simulate the lighting conditions over the period of the day. This simulation could be used to generate lighting conditions, shadows, color effects or other effects. This technique could also be used in Film/Theatrical modeling or could be used to generate special

effects in filmmaking. Such a system could also be used by a homeowner, for instance by selecting what they want their dwelling to look like from the outside and having lights be selected to produce that look. This is a possibility for safety when the owner is away.

Alternatively, the system could work in reverse where the owner turns on the lights in their house and a computer provides the appearance of the house from various different directions and
6 distances.

Although the above example discuss modeling for architecture, one of skill in the art would understand that any device, object, or structure where the effect of light on that device, object, or structure can be treated similarly.

Medical or other job simulation could also be performed. A lighting system according to the principles of the present invention may be used to simulate the lighting conditions during a
12 medical procedure. This may involve creating an operating room setting or other environment such as an auto accident at night, with specific lighting conditions. For example, the lighting on highways is generally high-pressure sodium lamps which produce nearly monochromatic yellow light and as a result objects and fluids may appear to be a non-normal color. Parking lots generally use metal halide lighting systems and produce a broad spectrum light that has spectral gaps. Any of these environments could be simulated using a system according to the principles
18 of the invention. These simulators could be used to train emergency personnel how to react in situations lit in different ways. They could also be used to simulate conditions under which any job would need to be performed. For instance, the light that will be experienced by an astronaut repairing an orbiting satellite can be simulated on earth in a simulation chamber.

Lights can also be used to simulate travel in otherwise inaccessible areas such as the light that would be received traveling through space or viewing astronomical phenomena, or lights

could be used as a three dimensional projection of an otherwise unviewable object. For instance, a lighting system attached to a computing device could provide a three dimensional view from the inside of a molecular model. Temporal Function or other mathematical concepts could also be visualized.

Optionally, the virtual environment can be generated by computer application that is a screen saver, which could be mapped into the real world lights in a room. As the screen saver creates and displays graphics on a computer screen, for example, the screen saver can create lighting effects outside of the computer screen. This could be used to create decorative effects or the lighting effects could be used to provide information or other effects. The information may represent computer, or network activity, for example, such that the activity is displayed in the lights and or the screen saver. This could include email activity, when an email is received by the system the lighting could change to a particular hue, saturation or intensity. The hue, saturation or intensity may change as more and more email is received.

A musical application could also be used, allowing for the choreographing of music to light, or the generation of light as a portion of the generation of music. Alternatively light could be used to help a user learn to play music. For instance light could be projected that indicates a particular key a user should press on a keyboard. In time, a user unable to read music could teach themselves to play instruments and music for the user's performance could be provided as light signals.

An embodiment of the present invention could be a puzzle that consists of getting the room lights into a particular configuration. You could put a person "inside" a real world Rubik's cube associated with a virtual Rubik's cube. An embodiment of the invention may be used in

flight simulators to change the ambient lighting conditions from day to night, or changing the lighting conditions as the horizon changes or associated with other aspects of the simulator.

A system according to the principles of the invention may also involve real-time simulation such as an actual motion inducing flight simulator, 3D motion rides (control through 3D libraries), or full mockup simulators where the lighting can be directly changed in response to what occurs. One example is that in a research submarine trainer the lighting within the submarine could be altered to remove red wavelengths as the sub dives because under water red light is often not present.

All articles, patents, and other references set forth above are hereby incorporated by reference. While the invention has been disclosed in connection with embodiments shown and described in detail, various equivalents, modifications, and improvements will be apparent to one of ordinary skill in the art from the above description